Extinguisher drying unit

DRY series

To quickly remove the moisture generated by the hydraulic testing inside extinguishers and cylinders



ADVANTAGES

Reduced dimensions and low power consumption make the DRY2 unit easy to use in the workshop or on-board a mobile a workshop.

The DRY6 unit ensures high productivity by drying several extinguishers at the same time.

COMPONENTS AND DEVICES

- > Lateral blower
- > Fast warming resistance
- > Insulated main manifold
- > Timer for work time setting
- > Main switchboard with 24V. controls

AVAILABLE MODELS

- > DRY2 single-phase
- > DRY6 three-phase

STANDARD EQUIPMENT

> User manual



Extinguisher drying unit





ACCESSORIES ON DEMAND

DESCRIPTION	MODEL	CODE
ACCESSORY FOR WHEELED EXTINGUISHERS	DRY2WE	AZEE002
ACCESSORY FOR WHEELED EXTINGUISHERS	DRY6WE	AZEE006

TECHNICAL FEATURES

MODEL	DRY2	DRY6/4	DRY6/10
CATALOGUE CODE	MZEE002	MZEE001	MZEE003
EXTINGUISHER PLACES	2	6	6
N° OF EXTINGUISHERS PER HOUR	12	36	48
(6 kg CAPACITY)			
WHEELED EXTINGUISHER PLACES WITH			
WE ACCESSORY	1	2	3
N° OF EXTINGUISHERS PER HOUR WITH			
WE ACCESSORY	2	4	8
VOLTAGE/FREQUENCY (VAC/Hz)	220/50	400/50	400/50
BLOWING POWER (kW)	0,37	1,1	1,5
RESISTANCE POWER (kW)	0,77	4	10
DIMENSIONS (Lxlxh) (mm)	870x370x685	2000x500x700	2000x500x700
WEIGHT (Kg)	30	70	75

PER MAGGIORI INFORMAZIONI:

> FOR FURTHER INFORMATION CONTACT:
POUR INFORMATIONS CONTACTER:

