

# High Pressure gas Cylinders ISO98-09 (PI marked) product range from Rama Cylinders

Pwent Ltd.

[www.pwent.eu](http://www.pwent.eu)

2017.10.15

Water capacity (liter+-5%)	Diameter (mm+-1%)	Length (approx. mm)	Weight (approx. kg)	Working pressure (bar)	Approval
4,5	140	450	8,8	200	ISO9809-1, 2010/35/EU, PI-marked
4,5	140	450	8,8	300	ISO9809-1, 2010/35/EU, PI-marked
4,8	140	460	9,1	200	ISO9809-1, 2010/35/EU, PI-marked
4,8	140	460	9,1	300	ISO9809-1, 2010/35/EU, PI-marked
5,0	140	475	9,3	200	ISO9809-1, 2010/35/EU, PI-marked
5,0	140	475	9,3	300	ISO9809-1, 2010/35/EU, PI-marked
5,5	140	510	9,5	200	ISO9809-1, 2010/35/EU, PI-marked
5,5	140	510	9,5	300	ISO9809-1, 2010/35/EU, PI-marked
6,0	140	540	10,1	200	ISO9809-1, 2010/35/EU, PI-marked
6,0	140	540	10,1	300	ISO9809-1, 2010/35/EU, PI-marked
6,0	168	405	11,0	200	ISO9809-1, 2010/35/EU, PI-marked
6,0	178	360	8,0	200	ISO9809-1, 2010/35/EU, PI-marked
6,5	140	590	10,8	200	ISO9809-1, 2010/35/EU, PI-marked
6,5	140	590	10,8	300	ISO9809-1, 2010/35/EU, PI-marked
6,5	168	430	11,5	200	ISO9809-1, 2010/35/EU, PI-marked
6,5	178	380	8,5	200	ISO9809-1, 2010/35/EU, PI-marked
6,7	140	605	11,0	300	ISO9809-1, 2010/35/EU, PI-marked
6,8	140	610	11,1	200	ISO9809-1, 2010/35/EU, PI-marked
6,8	140	610	11,1	300	ISO9809-1, 2010/35/EU, PI-marked
6,8	168	450	11,8	200	ISO9809-1, 2010/35/EU, PI-marked
7,0	140	630	11,4	200	ISO9809-1, 2010/35/EU, PI-marked
7,0	140	630	11,4	300	ISO9809-1, 2010/35/EU, PI-marked
7,0	168	460	12,0	200	ISO9809-1, 2010/35/EU, PI-marked
7,0	178	410	9,0	200	ISO9809-1, 2010/35/EU, PI-marked
7,5	140	660	11,9	200	ISO9809-1, 2010/35/EU, PI-marked
7,5	140	660	11,9	300	ISO9809-1, 2010/35/EU, PI-marked
7,5	168	485	12,5	200	ISO9809-1, 2010/35/EU, PI-marked
8,0	140	700	12,5	200	ISO9809-1, 2010/35/EU, PI-marked
8,0	140	700	12,5	300	ISO9809-1, 2010/35/EU, PI-marked
8,0	168	510	13,0	200	ISO9809-1, 2010/35/EU, PI-marked
8,0	178	450	10,0	200	ISO9809-1, 2010/35/EU, PI-marked
9,0	140	775	13,7	200	ISO9809-1, 2010/35/EU, PI-marked
9,0	140	775	13,7	300	ISO9809-1, 2010/35/EU, PI-marked
9,0	168	560	14,0	200	ISO9809-1, 2010/35/EU, PI-marked
9,0	178	495	10,8	200	ISO9809-1, 2010/35/EU, PI-marked
10,0	140	850	14,9	200	ISO9809-1, 2010/35/EU, PI-marked
10,0	140	850	14,9	300	ISO9809-1, 2010/35/EU, PI-marked
10,0	168	610	15,0	200	ISO9809-1, 2010/35/EU, PI-marked
10,0	178	540	11,8	200	ISO9809-1, 2010/35/EU, PI-marked
10,2	140	870	15,2	200	ISO9809-1, 2010/35/EU, PI-marked
10,2	140	870	15,2	300	ISO9809-1, 2010/35/EU, PI-marked
10,2	168	620	15,2	200	ISO9809-1, 2010/35/EU, PI-marked
10,5	140	890	15,5	200	ISO9809-1, 2010/35/EU, PI-marked
10,5	140	890	15,5	300	ISO9809-1, 2010/35/EU, PI-marked
11,0	140	925	16,1	200	ISO9809-1, 2010/35/EU, PI-marked
11,0	140	925	16,1	300	ISO9809-1, 2010/35/EU, PI-marked
11,0	168	660	16,0	200	ISO9809-1, 2010/35/EU, PI-marked
12,0	140	1000	17,2	200	ISO9809-1, 2010/35/EU, PI-marked
12,0	140	1000	17,2	300	ISO9809-1, 2010/35/EU, PI-marked
12,0	168	710	17,0	200	ISO9809-1, 2010/35/EU, PI-marked

Water capacity (liter+-5%)	Diameter (mm+-1%)	Length (approx. mm)	Weight (approx. kg)	Working pressure (bar)	Approval
12,0	178	625	13,5	200	ISO9809-1, 2010/35/EU, PI-marked
13,0	140	1075	18,2	200	ISO9809-1, 2010/35/EU, PI-marked
13,0	140	1075	18,2	300	ISO9809-1, 2010/35/EU, PI-marked
13,0	168	760	18,0	200	ISO9809-1, 2010/35/EU, PI-marked
13,4	140	1110	19,0	200	ISO9809-1, 2010/35/EU, PI-marked
13,4	140	1110	19,0	300	ISO9809-1, 2010/35/EU, PI-marked
13,4	168	780	18,2	200	ISO9809-1, 2010/35/EU, PI-marked
13,4	178	690	14,8	200	ISO9809-1, 2010/35/EU, PI-marked
13,4	204	585	18,0	200	ISO9809-1, 2010/35/EU, PI-marked
13,5	140	1115	19,2	200	ISO9809-1, 2010/35/EU, PI-marked
13,5	140	1115	19,2	300	ISO9809-1, 2010/35/EU, PI-marked
13,5	168	785	18,3	200	ISO9809-1, 2010/35/EU, PI-marked
14,0	140	1150	19,8	200	ISO9809-1, 2010/35/EU, PI-marked
14,0	140	1150	19,8	300	ISO9809-1, 2010/35/EU, PI-marked
14,0	168	810	19,2	200	ISO9809-1, 2010/35/EU, PI-marked
14,0	178	715	15,3	200	ISO9809-1, 2010/35/EU, PI-marked
14,0	204	610	18,5	200	ISO9809-1, 2010/35/EU, PI-marked
15,0	140	1225	21,0	200	ISO9809-1, 2010/35/EU, PI-marked
15,0	140	1225	21,0	300	ISO9809-1, 2010/35/EU, PI-marked
15,0	168	860	20,2	200	ISO9809-1, 2010/35/EU, PI-marked
15,0	178	760	16,0	200	ISO9809-1, 2010/35/EU, PI-marked
15,0	204	635	19,0	200	ISO9809-1, 2010/35/EU, PI-marked
16,0	140	1300	22,2	200	ISO9809-1, 2010/35/EU, PI-marked
16,0	140	1300	22,2	300	ISO9809-1, 2010/35/EU, PI-marked
20,0	168	1120	25,0	200	ISO9809-1, 2010/35/EU, PI-marked
20,0	178	980	20,5	200	ISO9809-1, 2010/35/EU, PI-marked
20,0	204	795	23,0	200	ISO9809-1, 2010/35/EU, PI-marked
20,0	229	670	26,5	200	ISO9809-1, 2010/35/EU, PI-marked
22,0	229	720	28,0	200	ISO9809-1, 2010/35/EU, PI-marked
23,6	178	1140	23,0	200	ISO9809-1, 2010/35/EU, PI-marked
25,0	178	1205	24,0	200	ISO9809-1, 2010/35/EU, PI-marked
25,0	204	965	28,0	200	ISO9809-1, 2010/35/EU, PI-marked
26,8	229	840	33,0	200	ISO9809-1, 2010/35/EU, PI-marked
27,0	229	850	33,5	200	ISO9809-1, 2010/35/EU, PI-marked
30,0	178	1425	29,0	200	ISO9809-1, 2010/35/EU, PI-marked
30,0	204	1135	32,0	200	ISO9809-1, 2010/35/EU, PI-marked
30,0	229	935	36,0	200	ISO9809-1, 2010/35/EU, PI-marked
34,0	229	1050	39,0	200	ISO9809-1, 2010/35/EU, PI-marked
34,0	267	820	44,0	200	ISO9809-1, 2010/35/EU, PI-marked
35,0	204	1305	36,0	200	ISO9809-1, 2010/35/EU, PI-marked
35,0	229	1070	40,0	200	ISO9809-1, 2010/35/EU, PI-marked
35,0	267	830	45,0	200	ISO9809-1, 2010/35/EU, PI-marked
40,0	204	1480	41,0	200	ISO9809-1, 2010/35/EU, PI-marked
40,0	229	1210	45,0	200	ISO9809-1, 2010/35/EU, PI-marked
40,0	267	935	50,0	200	ISO9809-1, 2010/35/EU, PI-marked
41,0	356	635	48,0	200	ISO9809-1, 2010/35/EU, PI-marked
42,0	356	645	49,0	200	ISO9809-1, 2010/35/EU, PI-marked
43,0	356	655	51,0	200	ISO9809-1, 2010/35/EU, PI-marked
45,0	204	1650	45,0	200	ISO9809-1, 2010/35/EU, PI-marked
45,0	229	1350	50,0	200	ISO9809-1, 2010/35/EU, PI-marked
45,0	267	1035	54,0	200	ISO9809-1, 2010/35/EU, PI-marked
45,0	356	665	53,0	200	ISO9809-1, 2010/35/EU, PI-marked
46,7	229	1395	51,5	200	ISO9809-1, 2010/35/EU, PI-marked
48,0	356	695	57,0	200	ISO9809-1, 2010/35/EU, PI-marked
50,0	204	1825	50,0	200	ISO9809-1, 2010/35/EU, PI-marked

Water capacity (liter+-5%)	Diameter (mm+-1%)	Length (approx. mm)	Weight (approx. kg)	Working pressure (bar)	Approval
50,0	229	1500	54,0	200	ISO9809-1, 2010/35/EU, PI-marked
50,0	267	1135	59,0	200	ISO9809-1, 2010/35/EU, PI-marked
50,0	356	720	59,0	200	ISO9809-1, 2010/35/EU, PI-marked
52,0	356	735	61,0	200	ISO9809-1, 2010/35/EU, PI-marked
53,0	356	750	62,0	200	ISO9809-1, 2010/35/EU, PI-marked
55,0	229	1620	59,0	200	ISO9809-1, 2010/35/EU, PI-marked
55,0	267	1250	65,0	200	ISO9809-1, 2010/35/EU, PI-marked
55,0	356	775	65,0	200	ISO9809-1, 2010/35/EU, PI-marked
57,0	356	795	67,0	200	ISO9809-1, 2010/35/EU, PI-marked
58,0	356	805	69,0	200	ISO9809-1, 2010/35/EU, PI-marked
60,0	229	1755	63,0	200	ISO9809-1, 2010/35/EU, PI-marked
60,0	267	1335	68,0	200	ISO9809-1, 2010/35/EU, PI-marked
60,0	356	830	70,0	200	ISO9809-1, 2010/35/EU, PI-marked
62,0	356	850	71,0	200	ISO9809-1, 2010/35/EU, PI-marked
63,0	356	860	72,0	200	ISO9809-1, 2010/35/EU, PI-marked
65,0	356	885	73,0	200	ISO9809-1, 2010/35/EU, PI-marked
67,5	267	1500	74,0	200	ISO9809-1, 2010/35/EU, PI-marked
68,0	267	1505	75,0	200	ISO9809-1, 2010/35/EU, PI-marked
70,0	356	940	77,0	200	ISO9809-1, 2010/35/EU, PI-marked
75,0	267	1630	80,0	200	ISO9809-1, 2010/35/EU, PI-marked
75,0	356	995	81,0	200	ISO9809-1, 2010/35/EU, PI-marked
78,0	356	1030	83,0	200	ISO9809-1, 2010/35/EU, PI-marked
80,0	267	1725	84,0	200	ISO9809-1, 2010/35/EU, PI-marked
80,0	356	1050	85,0	200	ISO9809-1, 2010/35/EU, PI-marked
82,0	356	1075	87,0	200	ISO9809-1, 2010/35/EU, PI-marked
85,0	356	1105	89,0	200	ISO9809-1, 2010/35/EU, PI-marked
90,0	267	1925	94,0	200	ISO9809-1, 2010/35/EU, PI-marked
90,0	356	1160	93,0	200	ISO9809-1, 2010/35/EU, PI-marked
95,0	356	1215	96,0	200	ISO9809-1, 2010/35/EU, PI-marked
100,0	356	1270	101,0	200	ISO9809-1, 2010/35/EU, PI-marked
105,0	356	1325	104,0	200	ISO9809-1, 2010/35/EU, PI-marked
110,0	356	1380	108,0	200	ISO9809-1, 2010/35/EU, PI-marked
115,0	356	1435	112,0	200	ISO9809-1, 2010/35/EU, PI-marked
120,0	356	1490	116,0	200	ISO9809-1, 2010/35/EU, PI-marked
125,0	356	1545	119,0	200	ISO9809-1, 2010/35/EU, PI-marked
130,0	356	1600	123,0	200	ISO9809-1, 2010/35/EU, PI-marked
135,0	356	1655	127,0	200	ISO9809-1, 2010/35/EU, PI-marked
140,0	356	1715	131,0	200	ISO9809-1, 2010/35/EU, PI-marked
145,0	356	1780	135,0	200	ISO9809-1, 2010/35/EU, PI-marked
150,0	356	1820	139,0	200	ISO9809-1, 2010/35/EU, PI-marked