
Dry powder transfer unit

TOTEM-M model

Compact dimensions Great performance



COMPONENTS AND DEVICES

- Single-phase electric suction exhauster for "M" version Pneumatic suction exhauster for "MP" version
- 2. Painted steel charge separator including:
 - a. high efficiency micro-porous special filter "Long-Life" type
 - micro-porous filter cleaning device by counter blowing
- 3. Powder down-flow valve with control pilot light
- Framework support with double position working/transport and wheels for movement
- 5. Handgrips in the upper framework
- Adjustment device for charge separator height and extinguishers replacement.

ADVANTAGES

"TOTEM-M" model shows an innovative design, conceived bearing in mind the operational tasks commonly encountered during maintenance of dry powder extinguishers.

A special attention has been paid to dimensions and weights in order to ease the unit transport, mainly fulfilling the on-site service operations.

By means of the slides (on demand) for vehicle installation, it is possible to install the equipment onboard a mobile workshop.

Thanks to the standard and optional available accessories, it is easy to get the best during the various operational steps ensuring the safest and most efficient use

"TOTEM-M" is made of high quality materials.

It is easy-to-use and requires low maintenance.

It has an optimum quality-price ratio that can satisfy the most demanding needs.

TOTEM-M in transport position

APPLICATIONS

TOTEM series units designed for extinguisher dry powder transfer (to whom "TOTEM-M" belongs) are suitable for filling and emptying powder fire extinguishers, both portable or wheeled types.

TOTEM range can fulfil all dry powder extinguishing system maintenance requirements, offering widest solutions: from the portable "TOTEM-M" (specially designed for mobile workshop), to the basic "TOTEM-E" up to the versatile "TOTEM-TS" (suitable for operating at mobile and fixed workshop), through to the multi-functional "TOTEM-GALAXY" and

"TOTEM-GALAXY II" (able to operate on-board powder tanks of fire fighting vehicles and /or on dry powder fixed tank).

There are also special solutions fulfilling industrial, airport or military needs. As an example, we point out models with pneumatic exhauster, "TOTEM-MP" and "TOTEM –TP".



Dry powder transfer unit



STANDARD ACCESSORIES



EASY TO BE MOVED



FILLING OF PORTABLE EXTINGUISHER



FILLING OF WHEELED EXTINGUISHER WITH VENTURI KIT

STANDARD ACCESSORIES

DESCRIPTION	CODE
Powder suction hose Ø 32 mm, 1500 mm long	ACC/TUB01
Suction pipe Ø 18 x 800 mm long	ACC/PES01
Suction pipe Ø 25 x 800 mm long	ACC/PES02
Aluminium/rubber adapters for fire extinguishers	ACC/ADA01 +
filling	ACC/ADA02
Drum for powder recovery, capacity 60 litres	ACC/BID01
Use and maintenance manual	

ACCESSORIES ON DEMAND

DESCRIPTION	CODE
Suction pipe \emptyset 25 x 1200 mm long, for wheeled extinguishers	
emptying	ACC/PES03
Supplementary drum for powder recovery, capacity 60 litres	ACC/BID01
Base with wheels for drum ACC/BID01	ACC/BID010
Extinguishers cone adapter Ø 45 ÷ 155 mm	ACC/ADA03
Remote filling kit VENTURI with cone adapter	ACC/VEN01
Remote filling kit VENTURI with 2" female adapter	ACC/VEN02
Electronic scale model ETW100 – ETW150	
Slides for fixed installation on-board the vehicle	MPM/BSS10

AVAILABLE MODELS AND TECHNICAL DETAILS

MODEL	TOTEM-M	TOTEM-MP
CATALOGUE CODE	MPME001	MPMP001
Powder flow rate (kg /min) (*) Varying according to dry powder density and working conditions	8 ÷ 12 (*)	10 ÷ 15 (*)
Voltage/ frequency Volt/Hz	230/50	-
Power kW	1,0	-
Compressed air supply (bar)	-	6 ÷ 8
Compressed air consumption (I/min)		380
Working position dimensions (wxlxh)-mm	560x580x1860	560x580x1860
Transport position dimensions (wxlxh)-mm	560x580x1080	560x580x1080
Weight (Kg)	35	35

PER MAGGIORI INFORMAZIONI:

> FOR FURTHER INFORMATION CONTACT:
POUR INFORMATIONS CONTACTER:

VANZETTI EQUIPMENT S.r.I. Vla Avv. Giovanni Agnelli, 10 12033 MORETTA (CN) ITALY Tel. +39 0172 915806 Fax +39 0172 915822



BULLETIN Nº VE/TOTEM M-R1.12-E